

HOOD TYPE DISHWASHERS



PRO TECH 811

The IFB wash system is able to manage a 60 second normal plate cycle with a theoretical productivity of more than 1000 plates/hour using the 22-plate rack (50x50cm). It also features a high temperature rinse at 80° C with guaranteed pressure, delivery and temperature. The electronic thermostop activates rinsing only if temperature matches that set. The hygiene of the working environment is implicit in the ProTech environmental protection concept. Guaranteed by SmartClean construction, the integral shock-proof plastic tank filter traps coarser residues while the Archimedes drain system reduces dirt deposited on the bottom of the tank.



STANDARD EQUIPMENT	
Plate rack (50 X 50 cm)	Yes
Flat rack (50 X 50 cm)	Yes
Cutlery container	Yes
Fill hose	Yes
Drain hose	Yes

TECHNICAL SPECIFICATIONS	
Dimensions (cm)	64 X 74 X 148
Rack size (cm)	50 X 50
Door opening (cm)	40
Max glass height (cm)	38
General construction	Single wall
Door construction	Single wall
Water consumption (L/Cycle)	2.7
Electrical Connection (V/Hz/ph)	400/50/3
Cycles (secs)	3 (60-120-150)

FEATURES		811
Easy lift hood		Yes
Fully moulded tank		Yes
ProStrain shock-proof composite material tank filter		Yes
Wash system with DuoFlo pump and equaliser arms		Yes
Archimedes drain system		Yes
Drain pump		Optional
Protect environment improvement system		Yes
ProSmart LED type electronic interface		Yes
No of standard wash programs		3
Prolong extra long wash program		Yes
Prolong intensive cycle		Yes
ProSelf—self clean cycle		Yes

HOOD TYPE DISHWASHERS

PRO TECH 813

Hood dishwasher with a hood opening of 40 cm, wash tank configuration permits washing of Gastronorm and Euronorm trays and also use of the special 22-plate 50 x 50 wire rack that boosts theoretical productivity to around 1,000 plates/hour. Fully moulded tank with ProStrain integral light composite material surface strainer, particularly resistant to impact and chemical attack; double filter on wash pump suction. Can be installed in line or in a corner configuration without the need for modifications or additional elements.



FEATURES		813
Easy lift hood		Yes
Fully moulded tank		Yes
ProStrain shock-proof composite material tank filter		Yes
Wash system with DuoFlo pump and equaliser arms		Yes
Archimedes drain system		Yes
Drain pump		Optional
Protect environment improvement system		Yes
ProSmart LED type electronic interface		Yes
No of standard wash programs		3
Prolong extra long wash program		Yes
Prolong intensive cycle		Yes
ProSelf—self clean cycle		Yes



STANDARD EQUIPMENT	
Plate rack (50 X 50 cm)	Yes
Flat rack (50 X 50 cm)	Yes
Cutlery container	Yes
Fill hose	Yes
Drain hose	Yes

TECHNICAL SPECIFICATIONS	
Dimensions (cm)	64 X 74 X 148
Rack size (cm)	50 X 50
Door opening (cm)	40
Max glass height (cm)	38
General construction	Single wall
Door construction	Single wall
Water consumption (L/Cycle)	2.5
Electrical connection (V/Hz/ph)	400/50/3
Cycles (secs)	3 (60-120-150)