

UNDER COUNTER GLASSWASHERS



FAST TECH 300

Extremely compact (total height of less than 65 cm) cup/glasswashers with 35 x 35 cm rack but with large load capacity (can wash up to 25 cm high glasses). It features a patented combined wash and rinse arm in heavy-duty composite material and adopts IFB's special Archimedes rinse technology which improves tank water refresh by more than 25%, guaranteeing cleaner water and consuming less detergent. Running costs are particularly low.

UNDER COUNTER GLASSWASHERS

FAST TECH 400

Glasswashers with 38.5 x 38.5 cm rack for washing up to 29.5 cm high glasses. It features a patented combined wash and rinse arm in heavy-duty composite material and IFB's special Archimedes rinse technology which improves tank water refresh by more than 25%, guaranteeing cleaner water and consuming less detergent. Running costs are particularly low.



STANDARD EQUIPMENT	
Flat rack (35 X 35 cm)	Yes
Cutlery container	Yes
Fill hose	Yes
Drain hose	Yes

TECHNICAL SPECIFICATIONS	
Dimensions (cm)	40 X 48 X 64
Rack size (cm)	35 X 35
Door opening (cm)	29
Max glass height (cm)	25
General construction	Single wall
Door construction	Double wall
Water consumption (L/Cycle)	2
Electrical connection (V/Hz/ph)	230/50/1
Cycles (secs)	1 (120)

FEATURES		300
Shock-proof plastic pump filter		Yes
Wash system with lower rotating arms		Yes
Archimedes drain system		Yes
Drain pump		Optional
Protect environment improvement system		Yes
Electro-mechanical interface		Yes
No of standard wash programs		1
Double skin insulated door		Yes

FEATURES		400
Shock-proof plastic pump filter		Yes
Wash system with lower rotating arms		Yes
Wash System with fixed upper arms		Yes
Archimedes drain system		Yes
Drain pump		Optional
Protect environment improvement system		Yes
Electro-mechanical interface		Yes
No of standard wash programs		1
Double skin insulated door		Yes

STANDARD EQUIPMENT	
Flat rack (38.5 X 38.5 cm)	Yes
Cutlery container	Yes
Fill hose	Yes
Drain hose	Yes

TECHNICAL SPECIFICATIONS	
Dimensions (cm)	44 X 64 X 70
Rack size (cm)	38.5 X 38.5
Door opening (cm)	32.5
Max glass height (cm)	29.5
General construction	Single wall
Door construction	Double wall
Water consumption (L/Cycle)	2.3
Electrical connection (V/Hz/ph)	230/50/1
Cycles (secs)	1 (120)

